NSN 5925-01-058-4968

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-058-4968

Body Style: Single pole type **Body Length:** Between 1.985 inches and 2.015 inches **Body Width:** Between 0.740 inches and 0.760 inches Case Material: Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.530 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: Between 1.650 inches and 1.670 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.890 inches **Pole Quantity:** 1 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac single location Operating Voltage Type And Rating Per Pole In Volts: 250.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 5000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic-hydraulic single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

NSN 5925-01-058-4968 Circuit Breaker - Page 2 of 2



Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.200 at 200 pct single location and 20.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and shock resistant and humidity resistant and vibration resistant and moisture resistant
Frequency In Hertz:
50.0 single location or 60.0 single location
Unpackaged Unit Weight:
2.200 ounces
Thread Series Designator:
Unc
Terminal Type And Quantity:
4 quick disconnect, male
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0