NSN 5925-01-058-6079



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-058-6079 **Body Style:** Multipole-single actuator type **Bushing Length:** 0.250 inches **Body Length:** 0.850 inches **Body Width:** 2.000 inches **Body Height:** 2.765 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.712 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.666 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: 0.712 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.862 inches **Fragility Factor:** Moderately rugged **Pole Quantity: Arc Quenching Method:** Air **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): **Maximum Continuous Load Current Rating Per Pole:** 5.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 800.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

NSN 5925-01-058-6079

Circuit Breaker - Page 2 of 2



Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
145.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.469 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
4.000 at 200 pct all locations and 35.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Shock resistant and vibration resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
400.0 all locations
Unpackaged Unit Weight:
0.350 pounds
Thread Series Designator:
Uns
Terminal Type And Quantity:
6 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0