

View Online at <https://aerobasegroup.com/nsn/5925-01-060-3002>

Body Length:

50.800 millimeters

Body Width:

23.370 millimeters

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

31.750 millimeters

Boss Height:

3.180 millimeters

Mounting Surface To Terminal End Distance:

48.140 millimeters

Pole Quantity:

1

Mounting Facility Type And Quantity:

Spring clip

Maximum Continuous Load Current Rating Per Pole:

10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.050 at 200 pct single location and 1.000 at 200 pct single location and 0.020 at 400 pct single location and 0.250 at 400 pct single location

Special Features:

Black body; neonilluminated handle; 100k, 1w resistorrequired for neon bulb

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0