NSN 5925-01-060-3002

Circuit Breaker - Page 1 of 2

Body Length: 50.800 millimeters Body Width:



View Online at https://aerobasegroup.com/nsn/5925-01-060-3002

23.370 millimeters
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
31.750 millimeters
Boss Height:
3.180 millimeters
Mounting Surface To Terminal End Distance:
48.140 millimeters
Pole Quantity:
1
Mounting Facility Type And Quantity:
Spring clip
Maximum Continuous Load Current Rating Per Pole:
10.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic:
Time delay single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location Trip Polary Time In Seconds Per Poted Continuous Currents
Trip Delay Time In Seconds Per Rated Continuous Current: 0.050, at 200 pct single location and 0.050, at 400 pct single location and 0.250, at 40
0.050 at 200 pct single location and 1.000 at 200 pct single location and 0.020 at 400 pct single location and 0.250 at 400 pct single location
ioodion

NSN 5925-01-060-3002

Circuit Breaker - Page 2 of 2

A030a0



Special Features:
Black body; neonilluminated handle; 100k, 1w resistorrequired for neon bulb
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: