

View Online at <https://aerobasegroup.com/nsn/5925-01-061-2999>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.000 inches

Overall Height:

1.625 inches

Overall Width:

1.540 inches

Case Material:

Plastic

Pole Quantity:

2

Mounting Facility Type And Quantity:

4 terminal

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Trip Delay Time In Seconds Per Rated Continuous Current:

0.250 at 200 pct all locations and 0.250 at 200 pct all locations

Special Features:

Illuminated handle

Frequency In Hertz:

60.0 all locations

Terminal Type And Quantity:

4 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0