NSN 5925-01-062-7359

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-062-7359

Body Style:

- Single pole type
- **Bushing Length:**
- 0.390 inches

Body Length:

0.750 inches

Body Width:

0.450 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.780 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

- 1.930 inches
- **Pole Quantity:**
- 1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

27

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location and 5.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

30.0 ac single location and 30.0 dc single location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

- 140.0 single location
- **Reset Method:**
- Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-062-7359

Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 push button
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
10.000 at 200 pct single location and 40.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
General purpose
Trip Release Ambient Tempurature Rating:
70.0 degrees fahrenheit single location
Frequency In Hertz:
60.0 single location
Unpackaged Unit Weight:
0.312 pounds
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 pin
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0