

View Online at <https://aerobasegroup.com/nsn/5925-01-062-7361>

Body Style:

Single pole type

Body Length:

Between 1.985 inches and 2.015 inches

Body Width:

Between 0.745 inches and 0.755 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.555 inches and 1.565 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.655 inches and 0.665 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.125 inches and 0.135 inches

Mounting Surface To Terminal End Distance:

Between 1.875 inches and 1.885 inches

Pole Quantity:

1

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

2 terminal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

0.190 at 200 pct single location and 1.900 at 200 pct single location

Inclosure Protection Type For Which Designed:

Fungus resistant and moisture resistant

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0