

View Online at <https://aerobasegroup.com/nsn/5925-01-063-4380>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

Between 0.332 inches and 0.380 inches

**Body Length:**

1.500 inches

**Body Width:**

1.250 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.594 inches and 0.656 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 0.344 inches and 0.406 inches

**Nonturn Device Location:**

At 3 oclock and at 9 oclock

**Nonturn Device Diameter:**

0.250 inches

**Fragility Factor:**

Moderately rugged

**Mounting Surface To Terminal End Distance:**

1.780 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac second location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc first location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 dc first location

**Circuit Protection Type:**

Overvoltage first location

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay second location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

120.0 first location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

Between pole one and two

**Internal Trip Release Configuration:**

Relay trip second location

**Thread Size:**

0.375 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.100 at 200 pct second location and 0.700 at 200 pct second location

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and shockproof and vibrationproof

**Frequency In Hertz:**

60.0 second location

**Unpackaged Unit Weight:**

3.600 ounces

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

5 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0