NSN 5925-01-064-4095

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-064-4095

Body Style:
Single pole type
Body Length:
2.500 inches
Body Width:
0.750 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
1.938 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
2.062 inches
End Application:
Flight service automated system (fsas)
Boss Height:
0.140 inches
Mounting Surface To Terminal End Distance:
2.611 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 threaded hole
Thready Qty Per Inch (tpi):
32
Maximum Continuous Load Current Rating Per Pole:
40.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
250.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
1000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Magnetic-hydraulic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Ultimate Trip Time Per Pole In Seconds:
10.000 single location
Reset Method:
Manual

NSN 5925-01-064-4095 Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
2.000 at 200 pct single location and 20.000 at 200 pct single location and 0.600 at 300 pct single location and 5.000 at 300 pct single
location and 0.300 at 400 pct single location and 2.000 at 400 pct single location and 0.005 at 1000 pct single location and 0.040 at 1000
pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant and moisture resistant
Frequency In Hertz:
50.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A030a0