NSN 5925-01-064-6283

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-064-6283

| Body Style: |
|---|
| Single pole type |
| Body Length: |
| 3.000 inches |
| Body Width: |
| 0.730 inches |
| Body Height: |
| 2.310 inches |
| Case Material: |
| Plastic |
| Fragility Factor: |
| Moderately rugged |
| Boss Height: |
| 0.250 inches |
| Pole Quantity: |
| 1 |
| Mounting Facility Type And Quantity: |
| 2 terminal |
| Storage Type: |
| General purpose warehouse |
| Features Provided: |
| Ground fault protection |
| Maximum Continuous Load Current Rating Per Pole: |
| 15.0 amperes ac single location |
| Operating Voltage Type And Rating Per Pole In Volts: |
| 120.0 ac single location |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: |
| 10000.0 ac single location |
| Circuit Protection Type: |
| Overcurrent single location |
| Trip Release Method: |
| Thermal-magnetic single location |
| Trip Release Characteristic: |
| Time delay single location |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: |
| 125.0 single location |
| Reset Method: |
| Manual |
| Main Contact Tripping Mechanism Type: |
| Trip free |
| Manual Actuator Type And Quantity: |

1 toggle

NSN 5925-01-064-6283 Circuit Breaker - Page 2 of 2



| Actuator Function: |
|--|
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 120.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| General purpose |
| Trip Release Ambient Tempurature Rating: |
| 25.0 degrees celsius single location |
| Frequency In Hertz: |
| 60.0 single location |
| Terminal Type And Quantity: |
| 1 clip and 1 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |