NSN 5925-01-065-7975

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-065-7975

Body Style:

Single pole type

Body Length:

2.844 inches

Body Width:

0.969 inches

Body Height:

2.359 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

2.840 inches

Unthreaded Mounting Hole Diameter:

0.188 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.062 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

10000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location and time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

NSN 5925-01-065-7975

Circuit Breaker - Page 2 of 2

Denot Methods
Reset Method:
Main Contact Tripping Mechanism Type:
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Switch Location And Position Designation:
External at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Switch Terminal Type:
Tab, solder lug
Switch Current Rating And Type In Amps:
6.0 ac and 0.25 dc
Switch Voltage Rating And Type In Volts:
240.0 ac and 250.0 dc
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0

