

View Online at <https://aerobasegroup.com/nsn/5925-01-068-2506>

Body Style:

Multipole-multiple actuator type

Body Length:

Between 1.938 inches and 2.032 inches

Body Width:

Between 2.218 inches and 2.282 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 1.518 inches and 1.592 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.718 inches and 0.782 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

Between 1.628 inches and 1.682 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.718 inches and 0.782 inches

Fragility Factor:

Moderately rugged

Boss Height:

Between 0.098 inches and 0.162 inches

Mounting Surface To Terminal End Distance:

Between 2.168 inches and 2.232 inches

Pole Quantity:

3

Arc Quenching Method:

Magnetic blowout

Mounting Facility Type And Quantity:

6 threaded hole

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

30.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

3 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At each pole

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.500 at 200 pct all locations and 20.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant

Frequency In Hertz:

60.0 all locations

Unpackaged Unit Weight:

7.500 ounces

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 solder stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0