

View Online at <https://aerobasegroup.com/nsn/5925-01-069-4815>

**Body Style:**

Multipole-multiple actuator type

**Body Length:**

5.840 inches

**Body Width:**

3.093 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

3.547 inches

**Center To Center Distance Between Terminals Parallel To Width:**

1.032 inches

**Unthreaded Mounting Hole Diameter:**

0.156 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

2.750 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

1.032 inches

**Fragility Factor:**

Moderately rugged

**Boss Height:**

0.219 inches

**Mounting Surface To Terminal End Distance:**

3.485 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

6 threaded stud and 6 unthreaded hole

**Storage Type:**

General purpose warehouse

**Special Handling Feature:**

Magnetic

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

30.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

3 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One, two, and three linked

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.138 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

40.000 at 200 pct all locations and 100.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Corrosion resistant and humidity resistant and fungus resistant and shock resistant and vibration resistant

**Special Features:**

Barrier, 0.120 in. H, on left side

**Frequency In Hertz:**

50.0 all locations or 60.0 all locations

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 threaded stud

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0