NSN 5925-01-069-9459

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-069-9459 **Body Style:** Single pole type **Overall Length:** 3.156 inches **Body Width:** 1.875 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.062 inches **Unthreaded Mounting Hole Diameter:** 0.250 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.406 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.156 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 900.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 130.0 single location **Reset Method:** Automatic

Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-069-9459

Circuit Breaker - Page 2 of 2



I rip De	elay Time in Seconds Per	Rated Continuous	Current:
20.000	at 200 pct single location		

Inclosure Protection Type For Which Designed:

Weatherproof

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0