## NSN 5925-01-070-0445



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-070-0445 **Body Style:** Multipole-single actuator type **Body Length:** 6.500 inches **Body Width:** 4.125 inches **Body Height:** 4.125 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 3.938 inches **Center To Center Distance Between Terminals Parallel To Width:** 1.375 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 3.312 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 1.375 inches **Boss Height:** 0.188 inches **Pole Quantity:** 3 **Mounting Facility Type And Quantity:** 4 threaded hole Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 440.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Instantaneous all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 

Ultimate Trip Rating Of Continuous Current
138.0 all locations

Reset Method:

Manual

## **NSN 5925-01-070-0445** Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Thread Size:
0.190 inches
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
50.0 degrees celsius all locations
Special Features:
Includes removable fuse unit assembly
Frequency In Hertz:
400.0 all locations
Thread Series Designator:
Unf
Terminal Type And Quantity:
6 clip and 3 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0