NSN 5925-01-070-3872



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-070-3872 **Body Style:** Single pole type **Body Length:** 4.750 inches **Body Width:** 1.026 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 3.547 inches **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.750 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.219 inches **Mounting Surface To Terminal End Distance:** 3.485 inches **Pole Quantity:** 1 **Mounting Facility Type And Quantity:** 2 threaded stud and 2 unthreaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 10.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Time delay single location

NSN 5925-01-070-3872 Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.138 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
40.000 at 200 pct single location and 100.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Corrosion resistant and humidity resistant and fungus resistant and shock resistant and vibration resistant
Special Features:
Barrier, 0.120 in. H, on left side
Frequency In Hertz:
50.0 single location or 60.0 single location
Thread Series Designator:
Unc
Terminal Type And Quantity:
2 threaded stud
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0