## NSN 5925-01-071-1747

Circuit Breaker - Page 1 of 2

Multipole-single actuator type

**Body Style:** 

0.380 inchesBody Length:1.500 inchesBody Width:1.250 inchesCase Material:

**Bushing Length:** 



View Online at https://aerobasegroup.com/nsn/5925-01-071-1747

Metal **Center To Center Distance Between Terminals Parallel To Length:** 0.875 inches **Center To Center Distance Between Terminals Parallel To Width:** 0.625 inches **Nonturn Device Radius:** 0.625 inches **Nonturn Device Length:** 0.140 inches **Nonturn Device Diameter:** 0.250 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.780 inches **Pole Quantity:** 2 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing w/panel seal Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 50.0 milliamperes ac second location **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 ac all locations

## NSN 5925-01-071-1747

Circuit Breaker - Page 2 of 2



Circuit Protection Type:
Overcurrent all locations
Trip Release Method:
Magnetic all locations
Trip Release Characteristic:
Time delay all locations
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 all locations
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
Between pole one and two
Internal Trip Release Configuration:
Series trip all locations
Thread Size:
0.375 inches
Trip Delay Time In Seconds Per Rated Continuous Current:
0.500 at 200 pct all locations and 11.000 at 200 pct all locations
Inclosure Protection Type For Which Designed:
Hermetically sealed and vibration resistant and shock resistant
Frequency In Hertz:
60.0 all locations
Unpackaged Unit Weight:
3.600 ounces
Thread Series Designator:
Unef
Terminal Type And Quantity:
4 wire hook
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0