

View Online at <https://aerobasegroup.com/nsn/5925-01-073-0849>

Body Style:

Multipole-single actuator type

Bushing Length:

Between 0.332 inches and 0.380 inches

Body Length:

Between 1.531 inches and 1.562 inches

Body Width:

Between 1.250 inches and 1.281 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

Between 0.875 inches and 0.906 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.594 inches and 0.656 inches

Mounting Surface To Terminal End Distance:

Between 1.797 inches and 1.828 inches

Pole Quantity:

2

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes ac all locations and 4.0 amperes dc all locations

Operating Voltage Type And Rating Per Pole In Volts:

240.0 ac all locations and 50.0 dc all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac all locations and 500.0 dc all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

Between pole one and two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.500 at 200 pct all locations and 9.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and hermetically sealed

Frequency In Hertz:

400.0 all locations

Unpackaged Unit Weight:

100.0 grams

Test Data Document:

81349-mil-prf-39019 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unef

Terminal Type And Quantity:

4 wire hook

Specification Data:

81349-mil-prf-39019/3 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0

Mil-std (military Standard):

Mil-prf-39019 spec.