# NSN 5925-01-074-3043

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-074-3043

## **Thread Pitch Diameters:**

+0.1177/+0.1214 inches

## **Body Style:**

Multipole-multiple actuator type

## **Body Length:**

2.490 inches

**Body Width:** 

#### 3.015 inches

Case Material:

#### Plastic

Center To Center Distance Between Terminals Parallel To Length:

#### 1.940 inches

Center To Center Distance Between Terminals Parallel To Width:

#### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

0.750 inches

## **Boss Height:**

0.150 inches

## Mounting Surface To Terminal End Distance:

2.491 inches

#### **Pole Quantity:**

4

## Mounting Facility Type And Quantity:

8 threaded hole

## Storage Type:

General purpose warehouse

#### **Special Handling Feature:**

Magnetic

## Thready Qty Per Inch (tpi):

32

## Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac third location

## **Operating Voltage Type And Rating Per Pole In Volts:**

250.0 ac third location

## Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac second location

#### **Circuit Protection Type:**

Overcurrent third location

## **Trip Release Method:**

Magnetic all locations

# NSN 5925-01-074-3043

Circuit Breaker - Page 2 of 2



**Trip Release Characteristic:** Time delay first location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 150.0 fourth location **Reset Method:** Manual Main Contact Tripping Mechanism Type: Trip free Manual Actuator Type And Quantity: 4 toggle **Actuator Function:** Trip-reset **Actuator Position Designation:** At each pole **External Actuator Linkage Arrangement:** One, two, three, and four linked Internal Trip Release Configuration: Shunt trip first location **Thread Size:** 0.138 inches Trip Delay Time In Seconds Per Rated Continuous Current: Any acceptable third location **Inclosure Protection Type For Which Designed:** Corrosion resistant and moisture resistant Frequency In Hertz: 60.0 third location **Thread Series Designator:** Unc **Terminal Type And Quantity:** 11 threaded stud Shelf Life: N/a Unit Of Measure: --**Demilitarization:** No Fiig: A030a0