

View Online at <https://aerobasegroup.com/nsn/5925-01-074-8588>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.495 inches

**Body Length:**

2.000 inches

**Body Width:**

2.250 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

1.530 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.750 inches

**Mounting Surface To Terminal End Distance:**

2.050 inches

**Pole Quantity:**

3

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

3.0 amperes ac second location

**Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc third location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac all locations and 1000.0 dc all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole two

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.500 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.800 at 200 pct all locations and 8.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Moisture resistant

**Frequency In Hertz:**

60.0 all locations

**Test Data Document:**

80063-sm-c-804677 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Thread Series Designator:**

Un

**Terminal Type And Quantity:**

6 quick disconnect, male

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0