

View Online at <https://aerobasegroup.com/nsn/5925-01-078-6450>

Body Style:

Single pole type

Bushing Length:

0.375 inches

Body Length:

1.562 inches

Body Width:

0.621 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Mounting Surface To Terminal End Distance:

1.700 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

Thd bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

1.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

250.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

300.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic-hydraulic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 single location

Ultimate Trip Time Per Pole In Seconds:

30.000 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.375 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.150 at 200 pct single location and 4.000 at 200 pct single location and 0.030 at 300 pct single location and 0.900 at 300 pct single location and 0.006 at 500 pct single location and 0.030 at 500 pct single location

Inclosure Protection Type For Which Designed:

Explosion proof and fungus resistant and moisture resistant

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0