

View Online at <https://aerobasegroup.com/nsn/5925-01-079-8416>

**Body Style:**

Single pole type

**Bushing Length:**

Between 0.280 inches and 0.380 inches

**Body Length:**

1.562 inches

**Body Width:**

0.625 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.906 inches

**Mounting Surface To Terminal End Distance:**

1.700 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Maximum Continuous Load Current Rating Per Pole:**

25.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

200.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

800.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

0.015 single location

**Reset Method:**

Automatic

**Internal Trip Release Configuration:**

Relay trip single location

**Thread Size:**

0.375 inches

**Trip Release Duty Cycle:**

Continuous single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

120.000 at 125 pct single location and 0.015 at 800 pct single location

**Inclosure Protection Type For Which Designed:**

Hermetically sealed

**Trip Release Ambient Temperature Rating:**

23.0 degrees celsius single location and 27.0 degrees celsius single location

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook and 3 pin

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0