

View Online at <https://aerobasegroup.com/nsn/5925-01-080-5005>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.060 inches

**Overall Height:**

2.000 inches

**Overall Width:**

0.920 inches

**Case Material:**

Plastic

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

Clamp

**Maximum Continuous Load Current Rating Per Pole:**

500.0 milliamperes ac single location

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 ac single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic-hydraulic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

0.200 single location and 7.000 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push button

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip single location

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.050 at 200 pct single location and 1.000 at 200 pct single location and 0.020 at 400 pct single location and 0.230 at 400 pct single location and 0.016 at 500 pct single location and 0.170 at 500 pct single location

**Special Features:**

Led in actuator

**Frequency In Hertz:**

50.0 single location

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A030a0