

View Online at <https://aerobasegroup.com/nsn/5925-01-083-3040>

Body Style:

Single pole type

Bushing Length:

0.380 inches

Body Length:

1.562 inches

Body Width:

0.625 inches

Case Material:

Metal

Center To Center Distance Between Terminals Parallel To Length:

0.875 inches

Switch Contact Arrangement:

Single pole, double throw

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

1.605 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Storage Type:

General purpose warehouse

Special Handling Feature:

Magnetic

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

16.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

50.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

500.0 dc single location

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Magnetic-hydraulic all locations

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

150.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.375 inches

Switch Location And Position Designation:

Internal at pole one

Inclosure Protection Type For Which Designed:

Hermetically sealed and shockproof and vibrationproof

Switch Terminal Type:

Pin

Switch Current Rating And Type In Amps:

10.0 ac and 3.0 dc

Switch Voltage Rating And Type In Volts:

250.0 ac and 50.0 dc

Unpackaged Unit Weight:

1.800 ounces

Thread Series Designator:

Unef

Terminal Type And Quantity:

2 wire hook

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0