

View Online at <https://aerobasegroup.com/nsn/5925-01-085-7028>

Body Style:

Multipole-single actuator type

Bushing Length:

0.250 inches

Body Length:

2.380 inches

Body Width:

1.100 inches

Body Height:

1.350 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

Between 0.673 inches and 0.735 inches

Center To Center Distance Between Terminals Parallel To Width:

Between 0.770 inches and 0.834 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

Thd bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

20.0 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

120.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

145.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

External Actuator Linkage Arrangement:

One, two, and three linked

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 20.000 at 200 pct all locations and 0.400 at 500 pct all locations and 2.000 at 500 pct all locations and 0.100 at 1000 pct all locations and 0.530 at 1000 pct all locations

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Un

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0