NSN 5925-01-087-7560

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-087-7560

Body Style:
Single pole type
Mounting Slot Width:
0.240 inches
Body Length:
6.310 inches
Body Width:
1.380 inches
Body Height:
3.380 inches
Case Material:
Plastic
Center To Center Distance Between Terminals Parallel To Length:
5.250 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:
4.620 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
1.140 inches
Boss Height:
0.156 inches
Pole Quantity:
1
1 Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 slot
Mounting Facility Type And Quantity: 4 slot Storage Type:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic:
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic: Instantaneous single location
Mounting Facility Type And Quantity: 4 slot Storage Type: General purpose warehouse Maximum Continuous Load Current Rating Per Pole: 20.0 amperes ac single location and 20.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 277.0 ac single location and 125.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location and 10000.0 dc single location Circuit Protection Type: Overcurrent single location Trip Release Method: Thermal-magnetic single location Trip Release Characteristic: Instantaneous single location Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

NSN 5925-01-087-7560

Circuit Breaker - Page 2 of 2



Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
40.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Terminal Type And Quantity:
2 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0