

View Online at <https://aerobasegroup.com/nsn/5925-01-087-8818>

**Body Style:**

Multipole-single actuator type

**Bushing Length:**

0.250 inches

**Body Length:**

1.840 inches

**Body Width:**

0.750 inches

**Body Height:**

1.530 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

0.704 inches

**Center To Center Distance Between Terminals Parallel To Width:**

0.624 inches

**Fragility Factor:**

Moderately rugged

**Pole Quantity:**

3

**Arc Quenching Method:**

Air

**Mounting Facility Type And Quantity:**

1 threaded bushing

**Storage Type:**

General purpose warehouse

**Cubic Measure:**

2.111 cubic inches

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

7.5 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

120.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

2000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

135.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Internal Trip Release Configuration:**

Series trip all locations

**Thread Size:**

0.469 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Humidity resistant

**Frequency In Hertz:**

400.0 all locations

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

6 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0