

View Online at <https://aerobasegroup.com/nsn/5925-01-088-6587>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

1.094 inches

Body Width:

0.781 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.704 inches

Fragility Factor:

Moderately rugged

End Application:

Mrap - rg-33

Mounting Surface To Terminal End Distance:

1.343 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing

Storage Type:

General purpose warehouse

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

25.0 amperes ac and 25.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac and 28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

2000.0 ac and 6000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.438 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

2.000 at 200 pct and 35.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Unpackaged Unit Weight:

0.067 pounds

Test Data Document:

81349-mil-c-5809 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Un

Terminal Type And Quantity:

2 tab w/screw

Specification Data:

96906-ms14105 government standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0