## NSN 5925-01-089-1958

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-089-1958

| Body Style:  |
|--|
| Single pole type   |
| Body Length:   |
| 2.000 inches   |
| Body Width:  |
| 0.750 inches   |
| Case Material:   |
| Plastic  |
| Center To Center Distance Between Terminals Parallel To Length:              |
| 1.530 inches   |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Length: |
| 1.660 inches   |
| Boss Height:   |
| 0.130 inches   |
| Mounting Surface To Terminal End Distance:                                   |
| 2.000 inches   |
| Pole Quantity:   |
| 1  |
| Mounting Facility Type And Quantity:   |
| 2 threaded hole  |
| Thready Qty Per Inch (tpi):  |
| 32   |
| Maximum Continuous Load Current Rating Per Pole:                             |
| 500.0 milliamperes dc single location  |
| Operating Voltage Type And Rating Per Pole In Volts:                         |
| 65.0 dc single location  |
| Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:      |
| 1000.0 dc single location  |
| Circuit Protection Type:   |
| Overcurrent single location  |
| Trip Release Method:   |
| Magnetic-hydraulic single location   |
| Trip Release Characteristic:   |
| Instantaneous single location  |
| Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:       |
| 125.0 single location  |
| Reset Method:  |
| Manual   |
| Main Contact Tripping Mechanism Type:  |
| Trip free  |
| Manual Actuator Type And Quantity:   |
| 1 toggle   |

## NSN 5925-01-089-1958

Circuit Breaker - Page 2 of 2



| Actuator Function:                            |
|---|
| Trip-reset                                    |
| Actuator Position Designation:                |
| At pole one                                   |
| Internal Trip Release Configuration:          |
| Shunt trip single location                    |
| Thread Size:                                  |
| 0.138 inches                                  |
| Inclosure Protection Type For Which Designed: |
| Moisture resistant                            |
| Thread Series Designator:                     |
| Unc   |
| Terminal Type And Quantity:                   |
| 2 quick disconnect, male                      |
| Shelf Life:                                   |
| N/a   |
| Unit Of Measure:                              |
| <del></del>                                   |
| Demilitarization:                             |
| No  |
| Fiig:   |
| A030a0  |
|   |