

View Online at <https://aerobasegroup.com/nsn/5925-01-089-2175>

Body Style:

Single pole type

Bushing Length:

0.250 inches

Body Length:

1.187 inches

Body Width:

0.798 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.850 inches

Mounting Surface To Terminal End Distance:

1.812 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

1 threaded bushing w/panel seal

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

5.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

115.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

600.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.400 inches

Trip Release Ambient Temperature Rating:

-40.0 degrees celsius single location and 71.0 degrees celsius single location

Frequency In Hertz:

400.0 single location

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0