NSN 5925-01-090-4112

Circuit Breaker - Page 1 of 2

Time delay single location



View Online at https://aerobasegroup.com/nsn/5925-01-090-4112

Body Style: Single pole type **Bushing Length:** 0.250 inches **Body Length:** Between 1.750 inches and 1.781 inches **Body Width:** Between 0.625 inches and 0.656 inches Case Material: **Plastic Center To Center Distance Between Terminals Parallel To Length:** 1.781 inches **Switch Contact Arrangement:** Single pole, double throw **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** Between 1.638 inches and 1.669 inches **Pole Quantity: Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 8.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:**

NSN 5925-01-090-4112

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
1 push-pull
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Auxiliary Switch Function And Quantity:
1 alarm
Internal Trip Release Configuration:
Series trip single location
Thread Size:
0.469 inches
Switch Location And Position Designation:
Internal at pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
0.006 at 200 pct single location and 0.020 at 200 pct single location
Inclosure Protection Type For Which Designed:
Explosion proof and fungus resistant
Switch Terminal Type:
Pin
Switch Current Rating And Type In Amps:
7.0 ac and 7.0 dc
Switch Voltage Rating And Type In Volts:
130.0 ac and 130.0 dc
Unpackaged Unit Weight:
0.125 pounds
Thread Series Designator:
Uns
Terminal Type And Quantity:
2 tab w/screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A030a0