## NSN 5925-01-090-4112

Circuit Breaker - Page 1 of 2



## View Online at https://aerobasegroup.com/nsn/5925-01-090-4112 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** Between 1.750 inches and 1.781 inches **Body Width:** Between 0.625 inches and 0.656 inches **Case Material:** Plastic Center To Center Distance Between Terminals Parallel To Length: 1.781 inches **Switch Contact Arrangement:** Single pole, double throw **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** Between 1.638 inches and 1.669 inches **Pole Quantity:** 1 Arc Quenching Method: Magnetic blowout Mounting Facility Type And Quantity: 1 threaded bushing Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 Maximum Continuous Load Current Rating Per Pole: 8.0 amperes dc single location **Operating Voltage Type And Rating Per Pole In Volts:** 32.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Magnetic single location **Trip Release Characteristic:** Time delay single location

Circuit Breaker - Page 2 of 2



Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

## **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

**Actuator Function:** 

Trip-reset

Actuator Position Designation:

At pole one

Auxiliary Switch Function And Quantity:

1 alarm

Internal Trip Release Configuration:

Series trip single location

Thread Size:

0.469 inches

Switch Location And Position Designation:

Internal at pole one

Trip Delay Time In Seconds Per Rated Continuous Current:

 $0.006\;$  at 200 pct single location and  $0.020\;$  at 200 pct single location

Inclosure Protection Type For Which Designed:

Explosion proof and fungus resistant

Switch Terminal Type:

Pin

Switch Current Rating And Type In Amps:

7.0 ac and 7.0 dc

Switch Voltage Rating And Type In Volts:

130.0 ac and 130.0 dc

**Unpackaged Unit Weight:** 

0.125 pounds

**Thread Series Designator:** 

Uns

**Terminal Type And Quantity:** 

2 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A030a0