## NSN 5925-01-092-3417

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-092-3417 **Body Style:** Single pole type **Bushing Length:** 0.250 inches **Body Length:** 1.781 inches **Body Width:** 0.750 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Length:** 0.704 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 1.218 inches **Pole Quantity: Mounting Facility Type And Quantity:** 1 threaded bushing Storage Type: General purpose warehouse Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 4.0 amperes ac single location and 4.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 120.0 ac single location and 30.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 2000.0 ac single location and 5000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 150.0 single location

**Reset Method:** Manual **Main Contact Tripping Mechanism Type:** Trip free

## NSN 5925-01-092-3417

Circuit Breaker - Page 2 of 2



| Manual Actuator Type And Quantity:                                     |
|------------------------------------------------------------------------|
| 1 push-pull                                                            |
| Actuator Function:                                                     |
| Trip-reset                                                             |
| Actuator Position Designation:                                         |
| At pole one                                                            |
| Internal Trip Release Configuration:                                   |
| Series trip single location                                            |
| Thread Size:                                                           |
| 0.469 inches                                                           |
| Trip Delay Time In Seconds Per Rated Continuous Current:               |
| 4.000 at 200 pct single location and 20.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed:                          |
| Corrosion resistant and vibration resistant and moisture resistant     |
| Trip Release Ambient Tempurature Rating:                               |
| 25.0 degrees celsius single location                                   |
| Frequency In Hertz:                                                    |
| 400.0 single location                                                  |
| Unpackaged Unit Weight:                                                |
| 62.0 grams                                                             |
| Thread Series Designator:                                              |
| Uns                                                                    |
| Terminal Type And Quantity:                                            |
| 2 tab w/screw                                                          |
| Shelf Life:                                                            |
| N/a                                                                    |
| Unit Of Measure:                                                       |
|                                                                        |
| Demilitarization:                                                      |
| No                                                                     |
| Fiig:                                                                  |
| A030a0                                                                 |
|                                                                        |
|                                                                        |