

View Online at <https://aerobasegroup.com/nsn/5925-01-092-9694>

Body Style:

Single pole type

Overall Length:

3.160 inches

Body Width:

1.880 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

1.060 inches

Unthreaded Mounting Hole Diameter:

Between 0.195 inches and 0.225 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

2.406 inches

Fragility Factor:

Moderately rugged

Mounting Surface To Terminal End Distance:

2.000 inches

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 unthreaded hole

Storage Type:

General purpose warehouse

Maximum Continuous Load Current Rating Per Pole:

90.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

28.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

575.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Automatic

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and salt spray proof and fungus resistant

Trip Release Ambient Temperature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 threaded stud

Specification Data:

58536-aa55571/07-008 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A030a0