NSN 5925-01-092-9694

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-092-9694 **Body Style:** Single pole type **Overall Length:** 3.160 inches **Body Width:** 1.880 inches **Case Material:** Plastic **Center To Center Distance Between Terminals Parallel To Length:** 1.060 inches **Unthreaded Mounting Hole Diameter:** Between 0.195 inches and 0.225 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:** 2.406 inches **Fragility Factor:** Moderately rugged **Mounting Surface To Terminal End Distance:** 2.000 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 unthreaded hole Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 90.0 amperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 28.0 dc single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 575.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent: 138.0 single location Reset Method: Automatic

Internal Trip Release Configuration:

Series trip single location

NSN 5925-01-092-9694

Circuit Breaker - Page 2 of 2



Trip Delay Time In Seconds Per Rated Continuous Current:

8.000 at 200 pct single location and 50.000 at 200 pct single location

Inclosure Protection Type For Which Designed:

Vibration resistant and shock resistant and salt spray proof and fungus resistant

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Terminal Type And Quantity:

2 threaded stud

Specification Data:

58536-aa55571/07-008 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0