

View Online at <https://aerobasegroup.com/nsn/5925-01-093-5959>

**Body Style:**

Multipole-multiple actuator type

**Mounting Slot Width:**

0.562 inches

**Body Length:**

3.344 inches

**Body Width:**

2.000 inches

**Body Height:**

2.312 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Width:**

1.000 inches

**Boss Height:**

0.156 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 slot

**Storage Type:**

General purpose warehouse

**Maximum Continuous Load Current Rating Per Pole:**

20.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

240.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

5000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Instantaneous all locations and time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

2 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At each pole

**External Actuator Linkage Arrangement:**

One and two linked

**Trip Delay Time In Seconds Per Rated Continuous Current:**

60.000 at 200 pct all locations and 300.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Fungus resistant

**Trip Release Ambient Temperature Rating:**

50.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Terminal Type And Quantity:**

2 clip and 2 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0