## NSN 5925-01-093-7558

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-093-7558
Body Style:
Single pole type
Body Length:
Between 2.990 inches and 3.010 inches
Body Width:
Between 0.720 inches and 0.740 inches
Body Height:
Between 2.570 inches and 2.590 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Boss Height:
Between 0.240 inches and 0.260 inches
Pole Quantity:
1
Arc Quenching Method:
Magnetic blowout
Mounting Facility Type And Quantity:
2 terminal
Storage Type:
General purpose warehouse
Maximum Continuous Load Current Rating Per Pole:
25.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal-magnetic single location
Trip Release Characteristic:
Instantaneous single location and time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
125.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:

1 toggle

## NSN 5925-01-093-7558

Circuit Breaker - Page 2 of 2



Actuator Function:
Trip-reset
Actuator Position Designation:
At pole one
Trip Delay Time In Seconds Per Rated Continuous Current:
120.000 at 200 pct single location
Inclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius single location
Frequency In Hertz:
60.0 single location
Test Data Document:
81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
1 clip and 1 screw
Specification Data:
81348-w-c-375/1 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A030a0