

View Online at <https://aerobasegroup.com/nsn/5925-01-093-9043>

Body Style:

Single pole type

Center To Center Distance Between Terminals Parallel To Length:

1.000 inches

Mounting Surface To Terminal End Distance:

1.343 inches

Pole Quantity:

1

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

4.0 amperes dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

0.45 dc single location

Circuit Protection Type:

Undervoltage single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole one

Thread Size:

0.437 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

0.055 at 100 pct single location and 0.115 at 100 pct single location

Trip Release Ambient Temperature Rating:

-55.0 degrees celsius single location and 121.0 degrees celsius single location

Special Features:

Threaded bushing w/panel seal type mount

Thread Series Designator:

Uns

Terminal Type And Quantity:

2 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0