

View Online at <https://aerobasegroup.com/nsn/5925-01-093-9043>

**Body Style:**

Single pole type

**Center To Center Distance Between Terminals Parallel To Length:**

1.000 inches

**Mounting Surface To Terminal End Distance:**

1.343 inches

**Pole Quantity:**

1

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

4.0 amperes dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

0.45 dc single location

**Circuit Protection Type:**

Undervoltage single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

138.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 push-pull

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Thread Size:**

0.437 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.055 at 100 pct single location and 0.115 at 100 pct single location

**Trip Release Ambient Temperature Rating:**

-55.0 degrees celsius single location and 121.0 degrees celsius single location

**Special Features:**

Threaded bushing w/panel seal type mount

**Thread Series Designator:**

Uns

**Terminal Type And Quantity:**

2 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0