# NSN 5925-01-093-9455

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-093-9455

## Body Style:

Multipole-multiple actuator type

## **Body Length:**

2.490 inches

# Body Width:

3.750 inches

#### **Case Material:**

Plastic

### Center To Center Distance Between Terminals Parallel To Length:

1.940 inches

### Center To Center Distance Between Terminals Parallel To Width:

### 0.750 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:

#### 2.060 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

### 0.750 inches

**Boss Height:** 

0.150 inches

Mounting Surface To Terminal End Distance:

2.475 inches

## **Pole Quantity:**

5

Mounting Facility Type And Quantity:

10 threaded hole

### Storage Type:

General purpose warehouse

### **Special Handling Feature:**

Magnetic

Thready Qty Per Inch (tpi):

32

### Maximum Continuous Load Current Rating Per Pole:

4.0 amperes dc fifth location

### **Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc fifth location

### Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations and 1000.0 dc all locations

### **Circuit Protection Type:**

Overcurrent all locations

### **Trip Release Method:**

Magnetic-hydraulic all locations

## **Trip Release Characteristic:**

Time delay all locations

# NSN 5925-01-093-9455

Circuit Breaker - Page 2 of 2



### Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

125.0 all locations

#### **Reset Method:**

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

5 toggle

**Actuator Function:** 

Trip-reset

**Actuator Position Designation:** 

At each pole

**External Actuator Linkage Arrangement:** 

One, two, three, four, and five linked

### Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.138 inches

### Trip Delay Time In Seconds Per Rated Continuous Current:

0.240 at 200 pct all locations and 0.800 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Corrosion resistant and moisture resistant

**Frequency In Hertz:** 

60.0 second location

## **Thread Series Designator:**

Unc

### **Terminal Type And Quantity:**

10 threaded stud

Shelf Life:

N/a

#### Unit Of Measure:

---

#### **Demilitarization:**

No

## Fiig:

A030a0