

View Online at <https://aerobasegroup.com/nsn/5925-01-095-5392>

**Body Style:**

Single pole type

**Bushing Length:**

0.380 inches

**Body Length:**

1.500 inches

**Body Width:**

0.625 inches

**Case Material:**

Metal

**Center To Center Distance Between Terminals Parallel To Length:**

Between 0.844 inches and 0.906 inches

**Switch Contact Arrangement:**

Single pole, double throw

**Mounting Surface To Terminal End Distance:**

1.605 inches

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

1 threaded bushing w/panel seal

**Thready Qty Per Inch (tpi):**

32

**Maximum Continuous Load Current Rating Per Pole:**

2.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

50.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

500.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Magnetic single location

**Trip Release Characteristic:**

Instantaneous single location and time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Auxiliary Switch Function And Quantity:**

1 alarm

**Internal Trip Release Configuration:**

Series trip single location

**Thread Size:**

0.375 inches

**Switch Location And Position Designation:**

Internal at pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

0.050 at 200 pct single location

**Inclosure Protection Type For Which Designed:**

Hermetically sealed and shock resistant and vibration resistant

**Switch Terminal Type:**

Wire hook

**Criticality Code Justification:**

Feat

**Switch Current Rating And Type In Amps:**

0.5 ac and 0.5 dc

**Switch Voltage Rating And Type In Volts:**

120.0 ac and 50.0 dc

**Special Features:**

High inrush trip time

**Thread Series Designator:**

Unef

**Terminal Type And Quantity:**

2 wire hook

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0