NSN 5925-01-096-4675



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-096-4675 **Body Style:** Single pole type **Body Length:** 6.310 inches **Body Width:** Between 1.370 inches and 1.380 inches **Body Height:** 3.380 inches **Case Material: Plastic Fragility Factor:** Moderately rugged **Boss Height:** 0.250 inches **Pole Quantity: Mounting Facility Type And Quantity:** 2 threaded hole Storage Type: General purpose warehouse **Special Handling Feature:** Magnetic Thready Qty Per Inch (tpi): 32 **Maximum Continuous Load Current Rating Per Pole:** 15.0 amperes ac single location **Operating Voltage Type And Rating Per Pole In Volts:** 120.0 ac single location Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

NSN 5925-01-096-4675 Circuit Breaker - Page 2 of 2



| Manual Actuator Type And Quantity: |
|----------------------------------------------------------------------------------------------------------------------------------------------------|
| 1 toggle |
| Actuator Function: |
| Trip-reset |
| Actuator Position Designation: |
| At pole one |
| Thread Size: |
| 0.138 inches |
| Trip Delay Time In Seconds Per Rated Continuous Current: |
| 2.000 at 200 pct single location |
| Inclosure Protection Type For Which Designed: |
| Corrosion resistant |
| Trip Release Ambient Tempurature Rating: |
| 40.0 degrees celsius single location |
| Frequency In Hertz: |
| 60.0 single location |
| Test Data Document: |
| 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification formation |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Designator: |
| Unc |
| Terminal Type And Quantity: |
| 2 compression |
| Specification Data: |
| 81348-w-c-375/10 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A030a0 |
| |
| |
| |
| |