

View Online at <https://aerobasegroup.com/nsn/5925-01-096-4694>

**Body Style:**

Multipole-single actuator type

**Mounting Slot Width:**

Between 0.178 inches and 0.198 inches

**Body Length:**

Between 5.990 inches and 6.010 inches

**Body Width:**

Between 2.740 inches and 2.760 inches

**Body Height:**

Between 3.365 inches and 3.385 inches

**Case Material:**

Plastic

**Center To Center Distance Between Terminals Parallel To Length:**

Between 5.052 inches and 5.072 inches

**Center To Center Distance Between Terminals Parallel To Width:**

Between 1.365 inches and 1.385 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Length:**

Between 4.490 inches and 4.510 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

Between 2.552 inches and 2.572 inches

**Boss Height:**

Between 0.115 inches and 0.135 inches

**Pole Quantity:**

2

**Mounting Facility Type And Quantity:**

2 slot

**Maximum Continuous Load Current Rating Per Pole:**

70.0 amperes ac all locations

**Operating Voltage Type And Rating Per Pole In Volts:**

480.0 ac all locations

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

14000.0 ac all locations

**Circuit Protection Type:**

Overcurrent all locations

**Trip Release Method:**

Thermal-magnetic all locations

**Trip Release Characteristic:**

Time delay all locations

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

125.0 all locations

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Manual Actuator Type And Quantity:**

1 toggle

**Actuator Function:**

Trip-reset

**Actuator Position Designation:**

At pole one

**Trip Delay Time In Seconds Per Rated Continuous Current:**

360.000 at 200 pct all locations

**Inclosure Protection Type For Which Designed:**

Dustproof

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius all locations

**Frequency In Hertz:**

60.0 all locations

**Test Data Document:**

81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 compression

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0