

View Online at <https://aerobasegroup.com/nsn/5925-01-097-0331>

Body Style:

Rectangular dimensional envelope

Overall Length:

6.312 inches

Overall Height:

3.812 inches

Overall Width:

4.125 inches

Case Material:

Plastic

Unthreaded Mounting Hole Diameter:

0.250 inches

End Application:

Ships service switchboard onboard 140 ft wtgb coast guard vessels

Pole Quantity:

3

Mounting Facility Type And Quantity:

4 unthreaded hole

Maximum Continuous Load Current Rating Per Pole:

80.0 amperes ac single location

Operating Voltage Type And Rating Per Pole In Volts:

600.0 ac single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

14000.0 ac single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Instantaneous single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

138.0 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 toggle

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Frequency In Hertz:

60.0 single location

Terminal Type And Quantity:

6 compression

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A030a0