

View Online at <https://aerobasegroup.com/nsn/5925-01-097-0334>

Body Style:

Rectangular dimensional envelope

Overall Length:

2.422 inches

Overall Height:

0.750 inches

Overall Width:

2.000 inches

Case Material:

Plastic

End Application:

D.C. Electrical panel onboard 41 ft utb coast guard vessels

Pole Quantity:

1

Mounting Facility Type And Quantity:

2 threaded hole

Maximum Continuous Load Current Rating Per Pole:

15.0 amperes dc single location

Operating Voltage Type And Rating Per Pole In Volts:

65.0 dc single location

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

1000.0 dc single location

Circuit Protection Type:

Overcurrent single location

Trip Release Method:

Thermal-magnetic single location

Trip Release Characteristic:

Time delay single location

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

1000.0 single location

Ultimate Trip Time Per Pole In Seconds:

0.004 single location and 0.025 single location

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Thread Size:

0.156 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

51.500 at 125 pct single location and 57.500 at 125 pct single location

Trip Release Ambient Temperature Rating:

40.0 degrees celsius single location

Thread Series Designator:

Unc

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0