

View Online at <https://aerobasegroup.com/nsn/5925-01-097-0334>

**Body Style:**

Rectangular dimensional envelope

**Overall Length:**

2.422 inches

**Overall Height:**

0.750 inches

**Overall Width:**

2.000 inches

**Case Material:**

Plastic

**End Application:**

D.C. Electrical panel onboard 41 ft utb coast guard vessels

**Pole Quantity:**

1

**Mounting Facility Type And Quantity:**

2 threaded hole

**Maximum Continuous Load Current Rating Per Pole:**

15.0 amperes dc single location

**Operating Voltage Type And Rating Per Pole In Volts:**

65.0 dc single location

**Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:**

1000.0 dc single location

**Circuit Protection Type:**

Overcurrent single location

**Trip Release Method:**

Thermal-magnetic single location

**Trip Release Characteristic:**

Time delay single location

**Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:**

1000.0 single location

**Ultimate Trip Time Per Pole In Seconds:**

0.004 single location and 0.025 single location

**Reset Method:**

Manual

**Main Contact Tripping Mechanism Type:**

Trip free

**Thread Size:**

0.156 inches

**Trip Delay Time In Seconds Per Rated Continuous Current:**

51.500 at 125 pct single location and 57.500 at 125 pct single location

**Trip Release Ambient Temperature Rating:**

40.0 degrees celsius single location

**Thread Series Designator:**

Unc

**Terminal Type And Quantity:**

6 screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A030a0