NSN 5925-01-099-0373

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-099-0373

Body Style:
Single pole type
Body Length:
3.344 inches
Body Width:
1.000 inches
Body Height:
2.312 inches
Case Material:
Plastic
Fragility Factor:
Moderately rugged
Boss Height:
0.250 inches
Pole Quantity:
1
Mounting Facility Type And Quantity:
2 terminal
Storage Type:
General purpose warehouse
Special Handling Feature:
Magnetic
Maximum Continuous Load Current Rating Per Pole:
20.0 amperes ac single location
Operating Voltage Type And Rating Per Pole In Volts:
240.0 ac single location
Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:
10000.0 ac single location
Circuit Protection Type:
Overcurrent single location
Trip Release Method:
Thermal-magnetic single location
Trip Release Characteristic:
Time delay single location
Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:
135.0 single location
Reset Method:
Manual
Main Contact Tripping Mechanism Type:
Trip free
Manual Actuator Type And Quantity:
••

1 toggle

NSN 5925-01-099-0373

Circuit Breaker - Page 2 of 2



At pole one Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location Inclosure Protection Type For Which Designed: Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Actuator Position Designation: At pole one Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location Inclosure Protection Type For Which Designed: Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain envir and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	ation format;
Trip Delay Time In Seconds Per Rated Continuous Current: 2.000 at 200 pct single location Inclosure Protection Type For Which Designed: Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
2.000 at 200 pct single location Inclosure Protection Type For Which Designed: Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Inclosure Protection Type For Which Designed: Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Corrosion resistant Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Trip Release Ambient Tempurature Rating: 40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
40.0 degrees celsius single location Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Frequency In Hertz: 60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
60.0 single location Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
Test Data Document: 81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
81348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environments.	ation format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain envir	ation format;
	•
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	ronmental
•••	
Terminal Type And Quantity:	
1 compression and 1 quick disconnect, male	
Specification Data:	
81348-w-c-375/13 government specification	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A030a0	