## NSN 5925-01-099-8648

Circuit Breaker - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5925-01-099-8648 **Body Style:** Multipole-single actuator type **Body Length:** 3.000 inches **Body Width:** 1.480 inches **Body Height:** 2.580 inches **Case Material: Plastic Center To Center Distance Between Terminals Parallel To Width:** 0.740 inches **Fragility Factor:** Moderately rugged **Boss Height:** 0.250 inches **Pole Quantity:** 2 **Arc Quenching Method:** Magnetic blowout **Mounting Facility Type And Quantity:** 4 terminal Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 60.0 amperes ac all locations **Operating Voltage Type And Rating Per Pole In Volts:** 240.0 ac all locations Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps: 10000.0 ac all locations **Circuit Protection Type:** Overcurrent all locations **Trip Release Method:** Thermal-magnetic all locations **Trip Release Characteristic:** Time delay all locations **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 125.0 all locations **Reset Method:** Manual

**Main Contact Tripping Mechanism Type:** Trip free

## **NSN 5925-01-099-8648** Circuit Breaker - Page 2 of 2



Manual Actuator Type And Quantity:
1 toggle
Actuator Function:
Trip-reset
Actuator Position Designation:
At pole two
Trip Delay Time In Seconds Per Rated Continuous Current:
360.000 at 200 pct all locations
nclosure Protection Type For Which Designed:
Fungus resistant
Trip Release Ambient Tempurature Rating:
25.0 degrees celsius all locations
Frequency In Hertz:
60.0 all locations
Test Data Document:
31348-w-c-375 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
2 clip and 2 screw
Specification Data:
31348-w-c-375/2 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A030a0