

View Online at <https://aerobasegroup.com/nsn/5925-01-100-5478>

Body Style:

Multipole-single actuator type

Bushing Length:

0.281 inches

Body Length:

1.100 inches

Body Width:

1.840 inches

Body Height:

1.561 inches

Case Material:

Plastic

Center To Center Distance Between Terminals Parallel To Length:

0.704 inches

Center To Center Distance Between Terminals Parallel To Width:

0.624 inches

Pole Quantity:

3

Mounting Facility Type And Quantity:

1 threaded bushing

Thready Qty Per Inch (tpi):

32

Maximum Continuous Load Current Rating Per Pole:

7.5 amperes ac all locations

Operating Voltage Type And Rating Per Pole In Volts:

200.0 ac all locations

Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:

5000.0 ac all locations

Circuit Protection Type:

Overcurrent all locations

Trip Release Method:

Thermal all locations

Trip Release Characteristic:

Time delay all locations

Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:

135.0 all locations

Reset Method:

Manual

Main Contact Tripping Mechanism Type:

Trip free

Manual Actuator Type And Quantity:

1 push-pull

Actuator Function:

Trip-reset

Actuator Position Designation:

At pole two

Internal Trip Release Configuration:

Series trip all locations

Thread Size:

0.469 inches

Trip Delay Time In Seconds Per Rated Continuous Current:

4.000 at 200 pct all locations and 20.000 at 200 pct all locations

Inclosure Protection Type For Which Designed:

Fungus resistant and shockproof and vibrationproof

Trip Release Ambient Temperature Rating:

25.0 degrees celsius all locations

Special Features:

Strengthened line terminals

Frequency In Hertz:

400.0 all locations

Thread Series Designator:

Uns

Terminal Type And Quantity:

6 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0