NSN 5925-01-102-1509



Circuit Breaker - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5925-01-102-1509 **Body Style:** Single pole type **Body Length:** 2.150 inches **Overall Diameter:** 0.750 inches **Case Material: Plastic Pole Quantity: Mounting Facility Type And Quantity:** 1 clip Storage Type: General purpose warehouse **Maximum Continuous Load Current Rating Per Pole:** 500.0 milliamperes ac single location and 500.0 milliamperes dc single location Operating Voltage Type And Rating Per Pole In Volts: 240.0 ac single location and 32.0 dc single location **Maximum Interrupting Capacity Current Type And Rating Per Pole In Amps:** 1000.0 ac single location and 1000.0 dc single location **Circuit Protection Type:** Overcurrent single location **Trip Release Method:** Thermal single location **Trip Release Characteristic:** Time delay single location **Ultimate Trip Rating Of Continuous Current Rating Per Pole In Percent:** 135.0 single location **Reset Method:** Manual **Main Contact Tripping Mechanism Type: Manual Actuator Type And Quantity:** 1 push button **Actuator Function:** Reset **Actuator Position Designation:**

At pole one

Internal Trip Release Configuration:

Series trip single location

Trip Delay Time In Seconds Per Rated Continuous Current:

3.500 at 200 pct single location and 9.500 at 200 pct single location

NSN 5925-01-102-1509

Circuit Breaker - Page 2 of 2



Inclosure Protection Type For Which Designed:

General purpose

Trip Release Ambient Tempurature Rating:

25.0 degrees celsius single location

Frequency In Hertz:

50.0 single location or 60.0 single location

Terminal Type And Quantity:

2 quick disconnect, male

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A030a0